



644.0345-OF

SCATOLA DA PARETE

122x120x90mm IP66 PULSANTE ON/OFF -
1NO+1NC TERMOINDURENTE

Certificati

TECHDATA		NORME E LEGGI
Serie commerciale	Serie ZENITH-P	EN 60079-31 (2014) [European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"
Tipologia prodotto	SCATOLA DA PARETE	IEC 60079-31 (2013) [International Standard] Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
Descrizione sintetica	SCATOLA DA PARETE	EN 60079-1 (2014) [European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures 'd'
Grado di protezione generico	Protetto da getti d'acqua	EN 60079-7 (2015) [European Standard] Explosive atmospheres. Equipment protection by increased safety "e"
Grado di protezione IP	IP66	IEC 60079-1 (2014) [International Standard] Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d".
Materiale	TERMOINDURENTE	IEC 60079-7 (2015) [International Standard] Explosive atmospheres - Part 7: Equipment protection by increased safety "e".
Equipment	Stazione di controllo	IEC 60079-0 (2017) [International Standard] Explosive atmospheres - Part 0: Equipment - General requirements
Funzione	PULSANTE ON/OFF - 1NO+1NC	EN 60079-0 (2018) [European Standard] Explosive atmospheres. General requirements.
Dimensioni	122x120x90mm	DIRECTIVE ATEX 2014/34/UE [European Directives] Atmosphere Explosive
Uscita cavo	1xM20	
Corrente nominale (valore)	16 A	
Categoria di utilizzo	AC12	
Tensione dim. nominale (Valore)	250 V	
Potenza massima dissipabile	1,660 W	
Gruppo e categorie EX	II 2GD	
Modo protezione gas	Ex db eb IIC T6 Gb	
Modo protezione polveri	Ex tb IIIC T80°C Db IP66	
Temperatura ambiente Ta		

min	-30 °C
Temperatura ambiente Ta max	40 °C