



590.EM3213

INTERR. DI MANOVRA /SEZIONATORE

32A 3P IP66/IP69 110x150x87mm Y1
EMERGENZA GIALLO/ROSSO GW 650°C IK09

Certificati

TECHDATA		NORME E LEGGI	
Tipologia prodotto	INTERR. DI MANOVRA /SEZIONATORE	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Serie commerciale	Serie ISOLATORS-TP	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Descrizione sintetica	INTERR. DI MANOVRA /SEZIONATORE	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Materiale	TECNOPOLIMERO	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Grado di protezione IP	IP66/IP69	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Tipo	EMERGENZA	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Colore	GIALLO/ROSSO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Corrente nominale	32A		
Poli	3P		
Taglia interruttore	Y1		
Tensione nominale	690V		
Dimensioni	110x150x87mm		
GLOW WIRE	GW 650°C		
Grado di protezione IK	IK09		
Flangia	106X150MM		