

PRODUCT DATASHEET

SMART+ BT FLEX 5M

SMART+ FLEX MULTICOLOR | Flexible LED strips for indoor use with Bluetooth technology



TECHNICAL DATA

Electrical data

| | |
|------------------------|---------------------|
| Nominal wattage | 16.00 W |
| Nominal voltage | 220...240 V |
| Nominal current | 120 mA |
| Power factor λ | > 0,50 |
| Operating mode | External LED driver |

Photometrical data

| | |
|--------------------------------------|---------------------------|
| Light color (designation) | RGBTW |
| Standard deviation of color matching | ≤ 6 sdc _m |
| Nominal luminous flux | 1100 lm |
| Luminous flux | 1100 lm |
| Luminous efficacy | 75 lm/W |
| Color temperature | 2000 ... 6500 K |
| Color rendering index Ra | > 80 |

Light technical data

| | |
|------------|-------|
| Beam angle | 110 ° |
|------------|-------|

Dimensions & weight



| | |
|----------------|------------|
| Product weight | 700.000 g |
| Length | 5000.00 mm |
| Width | 10.00 mm |
| Height | 2.60 mm |

Lifespan

| | |
|----------------------------|-------|
| Number of switching cycles | 15000 |
|----------------------------|-------|

Colors & materials

| | |
|---------------|-------------|
| Product color | Transparent |
| Body material | Silicone |

| | |
|----------------|--------------------|
| Cover material | Polycarbonate (PC) |
|----------------|--------------------|

Temperatures & operating conditions

| | |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
|---------------------------|--------------|

Additional product data

| | |
|-------------------|--------------|
| Show WEEE picto | Yes |
| Mounting location | All surfaces |



Capabilities

| | |
|----------------------------------|---------------------------------|
| Dimmable | Yes |
| Type of connection | Plug type C (EU) |
| Compatible smart home technology | Google Assistant / Amazon Alexa |
| ErP LEDmod replaceable | Not replaceable |

Certificates & standards

| | |
|-------------------------|-------------------------|
| Energy efficiency class | A++ |
| Standards | CE / EAC / REACH / RoHS |
| Protection class | II |
| Type of protection | IP20 |

DOWNLOAD DATA

| DOWNLOAD DATA | |
|--|--|
|  | User instruction SMART+ BT FLEX RGBTW |
|  | Declarations of conformity SMART BT FLEX 5M RGBTW |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075504844 | Folding box 1 | 62 mm x 230 mm x 205 mm | 897.00 g | 2.92 dm ³ |
| 4058075504851 | Shipping box 4 | 430 mm x 245 mm x 154 mm | 3914.00 g | 16.22 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.