



Part Number: 1583ENH

Category 5e Nonbonded-Pair Cable

Product Description

CAT5e (100MHz), 4-Pair, U/UTP Unshielded, Premise Horizontal Cable, 24 AWG solid bare copper conductors, Polyethylene insulation, LSZH jacket, RJ-45 compatible

Product Specifications

Technical Specifications

Application 1:	Horizontal and building backbone cable
Application 2:	Support current and future Category 5e applications, such as: 1000Base-T (Gigabit Ethernet), 100 Base-T, 10 Base-T, FDDI, ATM

Construction and Dimensions

Conductor:

Element	AWG	Stranding	Material	No. of Pairs
Individual pair	24	Solid	Bare copper	4
Min Elongation at Breakof Conductors:	10 %			

Insulation:

Element	Type	Material	Nominal Diameter
Individual pair	Dielectric	Polyethylene	0.9 mm
Min Elongation at Breakof Insulation:	100 %		

Color Chart 1:

Number	Color
Pair 1	White/Blue & Blue
Pair 2	White/Orange & Orange
Pair 3	White/Green & Green
Pair 4	White/Brown & Brown

Cabling 1:

Lay Length
4 pairs twisted together

Outerjacket 1:

Material	Nominal Diameter	Diameter +/- Tolerance
FRNC / LSNH	4.9 mm	0.3 mm
Min Elongation at Break of Jacket:	100 %	
Min Tensile Strength of Jacket:	9 MPa	

Electrical Characteristics

Conductor DCR:

Max. Conductor DCR	Max DCR Unbalanced Between Pairs [%]	Max. DCR Unbalanced Within Pair [%]
95 Ohm/km	4 %	2 Ohm

Capacitance:

Max. Capacitance Unbalance	Max. Mutual Capacitance
1,600 pF/m	56 pF/m
Min Insulation Resistance:	5000 mOhm/1000ft

Impedance:

Nominal Characteristic Impedance
100 Ohm

Delay:

Max. Delay Skew	Min. Velocity of Propagation
40 ns/100m	60 %

High Freq:

Element	Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Min. TCL [dB]	Min. ELTCTL [dB]
	1 MHz	2.1 db/100m	65.3 dB	62.3 dB	63.2 dB	60.2 dB	64 dB	61 dB	20 dB	40 dB	35 dB
	4 MHz	4 db/100m	56.3 dB	53.3 dB	52.32 dB	49.3 dB	52 dB	49 dB	23 dB	34 dB	23 dB
	10 MHz	6.3 db/100m	50.3 dB	47.3 dB	44 dB	41 dB	44 dB	41 dB	25 dB	30 dB	15 dB
	16 MHz	8 db/100m	47.2 dB	44.2 dB	39.2 dB	36.2 dB	39.9 dB	36.9 dB	25 dB	28 dB	10.9 dB
	20 MHz	9 db/100m	45.8 dB	42.8 dB	36.8 dB	33.8 dB	38 dB	35 dB	25 dB	27 dB	9 dB
	31.25 MHz	11.4 db/100m	42.9 dB	39.9 dB	31.5 dB	28.5 dB	34.1 dB	31.5 dB	23.6 dB	25.1 dB	5.5 dB
	62.5 MHz	16.5 db/100m	38.4 dB	35.4 dB	21.9 dB	18.9 dB	28.1 dB	25.1 dB	21.5 dB	22 dB	
	100 MHz	21.3 db/100m	35.3 dB	32.3 dB	14 dB	11 dB	24 dB	21 dB	20.1 dB	20 dB	

); Limits below 4MHz are for information only.

Current:

Max. Recommended Current [A]

1.5 A

Voltage:

Voltage Rating [V]

72 V

Use

Burning Load:	285 kJ/m
Max Recommended Pulling Tension:	65 N

Safety

ISO/IEC Flammability:	IEC 60332-1
Amt of Halogen IEC 60754-1 / EN50267-1:	Zero
Amt of Halogen Acid Gas; MaxConductivity:	10 μ S/mm
Amt of Halogen Acid Gas; Min pH:	4.3
Smoke Density; Min Transmittance:	60 %

Temperature Range

Installation Temp Range:	0 to +50 °C
Operating Temp Range:	-30 to +60 °C

Mechanical Characteristics

Min Bend Radius During Installation:	40 mm
--------------------------------------	-------

Min Bend Radius During Operation:	20 mm
-----------------------------------	-------

Part Number

Standards

ISO/IEC Compliance:	ISO/IEC 11801 2nd edition (2002) and ISO/IEC 11801 Amendment 2 (2010)
ANSI Compliance:	ANSI/TIA/EIA 568-B.2-1 (2002)
CENELEC Compliance:	EN 50173-1 (2011)

History

Revision Date:	2015-03-09
Revision Number:	3

Product Variants

Part Number	Color	Put-Up Type	Length
1583ENH.001000	GRAY	Reel	1000 m
1583ENH.00305	GRAY	Reel	305 m
1583ENH.003570	GRAY, RAL 7032	Reel	
1583ENH.00500	GRAY	Reel	500 m
1583ENH.00B100	GRAY	Flat Box	100 m
1583ENH.00U305	GRAY	UnReel	305 m
1583ENH.01305	BLUE	Reel	305 m
1583ENH.01500	BLUE	Reel	500 m
1583ENH.01U305	BLUE	UnReel	305 m
1583ENH.02U305	GREEN	UnReel	305 m
1583ENH.03U305	YELLOW, RAL 1021	UnReel	305 m
1583ENH.04500	ORANGE	Reel	500 m
1583ENH.04U305	ORANGE	UnReel	305 m
1583ENH.05U305	VIOLET	UnReel	305 m
1583ENH.07500	RED	Reel	500 m
1583ENH.07U305	RED	UnReel	305 m
1583ENH.08U305	GRAY	UnReel	305 m
1583ENH.09U305	WHITE	UnReel	305 m
1583ENH.10U305	BLACK	UnReel	305 m

© 2016 Belden, Inc.

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of

such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.