



Solar Charging



MALIS XL

Lampada solare da terra per esterno con rilevatore di movimento
 LED solar garden light with motion sensor
 Lampe de jardin LED solaire sur pied avec détecteur de mouvements
 LED luz de jardín solar con sensor de movimiento
 LED Solar Gartenleuchte mit Bewegungsmelder

SL420



PACKING	INNER	MASTER
/	pcs	pcs
Colour box	6	6



DATI TECNICI / SPECIFICATION / CARACTÉRISTIQUES / CARACTERISTICAS / SPEZIFIKATIONEN

Codice / Item / Code / Código / Code	SL420
Nome prodotto / product name / Nom du produit / Designación / Produktname	MALIS XL
Alimentazione / Power supply / Alimentation / Alimentación / Stromversorgung	Monocrystalline solar panel: 5.5V 90mA
Batteria / Battery / Batterie / Batería / Batterie	3.7V 1200mAh 18650 Li-ion type (included)
Tempo di ricarica / Charging Time / Temps de recharge / Tiempo de carga / Ladezeit	8 hrs
Autonomia / Runtime / Autonomie / Autonomía / Leuchtdauer	6 hrs (continuous use)
Tecnologia della Luce / Light technology / Technologie de la lumière / Tecnología de iluminación / Leuchtentechnologie	3 x SMD LED
Potenza d'illuminazione (W) / (W) Power / Puissance (W) / Potencia (W) / Leuchtstärke (W)	2,2W
Consumo elettrico (W) / (W) Consumption / Consommation (W) / Consumo (W) / Verbrauch (W)	2,2W
Lumen / Lumen / Lumen / Lumen / Lumen	220 Lm
Tipo di luce / Kelvin degrees / Degrés Kelvin / Temperatura de luz / Grad Kelvin	6000K
IRC / Colour rendering Index / Indice de rendu des couleurs / IRC / Farbwiedergabeindex	-
Fascio di luce / Light beam / Type de faisceau / Tipo de haz / Lichtstrahl	Diffuse Light
Portata / Range / Distance d'éclairage / Alcance alumbrado / Leuchtweite	-
Durata di vita del LED / LED Life time / Durée de vie des LED / Durada de vida del LED / Lebensdauer LED	15.000
Massima intensità del fascio / Peak beam intensity / Intensité maximale du faisceau / Máxima intensidad / Abstrahlintensität	-
Dimmerabilità / Dimmable / Dimmable / Dimmer, regulador / Dimmereigenschaften	-
Numero di cicli on-off / On off cycles / Nr de cycles on-off / Numero de On-OFF / Ein-Aus Zyklen	-
Power factor / Power factor / Power factor / Power factor / Leistungsfaktor	-
Cavo / Cable / Câble / Cable / Kabel	-
Materiale / Material / Matériau / Material / Material	Plastic + Steel
Grado di protezione / Protection degree / Degré de protection / Estanqueidad / Schutzgrad	IP44
Resistenza Meccanica / Mechanical resistance / Résistance Mécanique / Resistencia mecanica / Mechanische Widerstandsfähigkeit	-
Accessori inclusi / Accessories included / Accessoires fournis / Accesorios incluidos / Zubehör enthalten	2 screws + spike
Funzioni / Functions / Fonctions / Función / Funktionen	-
Dimensioni prodotto / Product dimensions / Dimensions du produit / Dimensiones producto / Abmessungen Produkt	Width x Height x Length: 160 ø x 463 mm
Dimensioni prodotto imballato / Packed dimensions / Dimensions du produit emballé / Dimensiones embalaje / Abmessungen Umverpackung	Width x Height x Length: 155 x 155 x 480 mm
Peso netto / Net Weight / Poids net / Peso neto / Gewicht netto	670 g
Peso prodotto imballato / Weight of packaged product / Poids du produit emballé / Peso producto con embalaje / Gewicht mit Umverpackung	865 g