




relé ad impulsi meccanico

STEP RELAY



50-60 Hz - 12, 24, 230 Vac
 Installazione a parete
 Incasso libero
 Carico nominale 10 A / 250 Vac

50-60 Hz - 12, 24, 230 Vac
 Wall fixing
 Free recessed
 Rated load 10 A / 250 V



1 contatto
 2 sequenze

1 contact
 2 sequences



2 contatti
 4 sequenze

2 contacts
 4 sequences



CODICE	TENSIONE	INCANDESCENZA	ALOGENA	FLUORESCENZA	LED 230V	PULSANTI LUMINOSI COLLEGABILI	CONTATTI	SCHEMI	PESO	
CODE	VOLTAGE	INCANDESCENT	HALOGEN	FLUORESCENT	LED 230V	ILLUMINATED PUSH-BUTTONS	CONTACTS	DIAGRAMS	WEIGHT	
	Vac	Watt	Watt	Watt	Watt				gr	
RE012IN	12	1000	700	350	100*	4	1 NO	A	55	
RE024IN	24	1000	700	350	100*	4	1 NO	A	55	
RE230IN	230	1000	700	350	100*	4	1 NO	A	55	
RE012CO	12	1000	700	350	100*	4	2 NO	B	55	
RE024CO	24	1000	700	350	100*	4	2 NO	B	55	
RE230CO	230	1000	700	350	100*	4	2 NO	B	55	
CO250RE	condensatore 1,5 uF / 250 Vac fino a 25 pulsanti collegabili									10