






RELÉ AD IMPULSI MECCANICO

STEP RELAY



50-60 Hz - 12, 24, 230 Vac
 Installazione a parete
 Incasso libero
 Carico nominale 10 A / 250 Vac

50-60 Hz - 12, 24, 230 Vac
 Wall fixing
 Free recess
 Rated load 10 A / 250 V



CODICE	TENSIONE	INCANDESCENZA	ALOGENA	FLUORESCENZA	LED	PULSANTI LUMINOSI COLLEGABILI	CONTATTI	SCHEMI	PESO	QUANTITA'
CODE	VOLTAGE	INCANDESCENT	HALOGEN	FLUORESCENT	LED	ILLUMINATED PUSH-BUTTON	CONTACT	DIAGRAM	WEIGHT	QUANTITY
	Vac	Watt	Watt	Watt	230Watt				gr	
RE 012 IN	12	1000	700	350	100*	4	1 NO	A	55	10
RE 024 IN	24	1000	700	350	100*	4	1 NO	A	55	10
RE 230 IN	230	1000	700	350	100*	4	1 NO	A	55	10
RE 012 CO	12	1000	700	350	100*	4	2 NO	B	55	10
RE 024 CO	24	1000	700	350	100*	4	2 NO	B	55	10
RE 230 CO	230	1000	700	350	100*	4	2 NO	B	55	10
CO 250 RE	condensatore 1,5 uF / 250 Vac fino a 25 pulsanti collegabili								10	200