


## Accessori Accessories

### Curve a 90° non filettabili 6013 Non-threadable 90° elbows 6013



La particolare cura nella finitura degli imbocchi, assicura un perfetto infilaggio dei cavi senza rischio di danneggiamento del rivestimento. Normalmente sono utilizzate quando le esigenze di installazione non consentono la curvatura del tubo in opera. Continuità elettrica garantita

The particular care in the finishing of the inlets, ensures a perfect threading of cables without risk of damage to the coating. They are normally used when the installation requirements do not allow bending the conduit on site. Electrical continuity guaranteed

- Standard CEI EN 61386 e 61386-21
- Grado IP del sistema IP66/IP68/IP69

- Standards IEC EN61386-1 and 61386-21
- System protection degree IP66/IP68/IP69


#### Acciaio zincato Galvanized steel

CODICE CODE	DIAMETRO NOMINALE NOMINAL DIAMETER	S	DIMENSIONI mm DIMENSIONS mm				CONFEZIONE PACKAGE pz / pcs.
	ØD mm		Ø PU	E	R	L	
6013-16L	16	1,0	14,0	100	40,0	150	5
6013-20L	20	1,0	18,0	100	50,0	155	5
6013-25L	25	1,2	22,5	100	62,5	180	5
6013-32L	32	1,2	29,5	100	80,0	200	5
6013-40	40	1,2	37,5	100	100,0	240	5
6013-50	50	1,2	47,5	170	170,0	370	1
6013-63	63	1,5	60,0	200	230,0	460	1

#### Acciaio Inox Stainless steel

AISI 304 CODICE CODE	AISI 316L CODICE CODE	DIAMETRO NOMINALE NOMINAL DIAMETER	S	DIMENSIONI mm DIMENSIONS mm				CONFEZIONE PACKAGE pz / pcs.
		ØD mm		Ø PU	E	R	L	
6013-16X	-	16	1,0	14,0	100	46,0	155	5
6013-20X	6013-20XX	20	1,0	18,0	110	67,0	195	5
6013-25X	6013-25XX	25	1,2	22,5	125	82,0	225	5
6013-32X	6013-32XX	32	1,2	29,5	150	112,0	285	5
6013-40X	6013-40XX	40	1,2	37,5	150	190,0	360	5
6013-50X	6013-50XX	50	1,2	47,5	175	250,0	450	1
6013-63X	6013-63XX	63	1,5	60				1

### Testacanna 6097L Bushing 6097L



Sono prodotti in materiale plastico PE-LD privo di alogeni e sono applicati alle estremità dei tubi metallici per evitare il contatto diretto tra i cavi e gli spigoli del tubo durante le operazioni di infilaggio. Colore Grigio RAL 7035

Manufactured in halogen-free PE-LD plastic, applied to the end of the metal conduits to prevent direct contact between the cables and the corners of the conduit during insertion operations. Colour Grey RAL 7035

CODICE CODE	DIAMETRO NOMINALE NOMINAL DIAMETER	DIMENSIONI mm DIMENSIONS mm		CONFEZIONE PACKAGE pz / pcs.
	ØD mm	Ø PU mm		
6097L16B	16		14,0	100
6097L20B	20		18,0	100
6097L25B	25		22,5	100
6097L32B	32		29,5	50
6097L40B	40		37,5	50
6097L50B	50		47,5	25
6097L63B	63		60,0	20

