

**407.3287****INTERLOCKED SOCKET**

32A 3P+N+E 6h 346-415V 60Hz 50Hz  
103X230MM Screw terminals With  
mechanical interlock



EN 60309-1/A1 (2007)  
EN 60309-1 (1999)  
EN 60309-2 (1999)  
EN 60309-1/A2 (2012)  
EN 60309-2/A1 (2007)  
EN 60309-2/A2 (2012)  
EN 60309-4 (2007)  
EN 60309-4/A1 (2012)

Low voltage direct. 2014/35/EU  
DIRECTIVE RoHS 2011/65/EU

Commercial Series

PROXIMA Series

Synthetical description

INTERLOCKED SOCKET

Mounting version

FLUSH MOUNTING

**■ TECHNICAL CHARACTERISTICS**

Rated current	32A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

**■ PHYSICAL CHARACTERISTICS**

Mounting version	FLUSH MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK10
Contact material	CuZn (brass)
Padlock	ø5mm

**■ DIMENSIONAL CHARACTERISTICS**

Flange	103X230MM
--------	-----------

**■ DOWNLOAD**

BIM Object  
[Technical drawing \[PDF\]](#)  
[Technical drawing \[DWG\]](#)  
[Technical drawing \[STP\]](#)  
[Instruction manual](#)

**■ OPTIONS & VARIOUS NOTES**

Options	With mechanical interlock
Notes	WITHOUT FUSE HOLDER