# GENERAL CATALOGUE

# L4003TL

Touchless switch for lighting. Allows to control light sources by simply passing the hand in front of the switch. Detection distance 6 cm. LED indicator light, activated by default (can be switched off). Mechanism depth 20 mm, compatible with all types of flush-mounting boxes. 2 possibilities of cabling : • With neutral, 3 wires. Accepted power by lamp type: - LEDs and CFL lamps: 200W LED - Incandescent and halogen lamps: 200W - LEDs, CFLs, halogen lamps, fluorescent tubes with ferromagnetic or electronic transformer: 200VA • Without neutral, 2 wires. Accepted power by lamp type: - LEDs and CFL lamps: 5 to 200W LED - Incandescent and halogen lamps: 5 to 200W - LEDs, CFLs, halogen lamps, fluorescent tubes with ferromagnetic or electronic transformer: 5 to 200VA. • 4 modes available: - 1-way switch mode: wiring with or without neutral - 2-way switch mode: wiring with neutral mandatory - Master/Slave mode: wiring with neutral mandatory, 3 slaves max. - Push-button mode: wiring with neutral mandatory, for controlling relays or a «with Netatmo» micromodule. 2 modules.

## Technical features

| | |
|---|---|
| Brand | BTicino |
| Rated power (W) | 200W |
| Rated power (VA) | 200VA |
| Modules | 2 |
| Series | Livinglight |

## Commercial data

| | |
|---|---|
| Minimum quantity | 1 |
| Sales unit | 1 |
| EAN code | 8005543741191 |

*Source page:* *https://catalogue.bticino.com/product/solution-for-residential-and-tertiary-building/livinglight/electronic-control-devices/BTI-L4003TL-EN*