



402.3286-F

PRESA INTERBLOCCATA

32A 3P+T 6h 380-415V 50Hz 60Hz
130X260MM Morsetti a vite Con interblocco meccanico

Certificati

TECHDATA		NORME E LEGGI	
Tipologia prodotto	PRESA INTERBLOCCATA	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Serie commerciale	Serie ADVANCE-GRP	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descrizione sintetica	PRESA INTERBLOCCATA		
Corrente nominale	32A		
Poli	3P+T	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Riferimento Orario	6h	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Tensione nominale (range)	250-400V		
Tensione nominale	380-415V	EN 60309-4 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock
Frequenza d'impiego	60Hz		
Frequenza d'impiego	50Hz	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Colore	ROSSO		
Materiale	GRP Glass Reinforced Polyester		
Grado di protezione generico	Stagno all'immersione		
Grado di protezione IP	IP66/IP67/IP69		
Grado di protezione IK	IK10		
Morsetti	Morsetti a vite		
Materiale di contatto	CuZn (ottone)		
Flangia	130X260MM		

Temperatura di esercizio	-40°C/+60°C
GLOW WIRE	GW 960°C
Autoestinguenza UL94	V0
Opzioni	Con interblocco meccanico
Note	CON BASE PORTAFUSIBILI
Lucchetto	ø5mm