

### FASCETTE IN NYLON 6.6 - NYLON 6.6 CABLE TIES



Articolo/Colore Type/Color		Dimensioni mm Dimension mm		Ø Max mm di serraggio	Resistenza min. alla trazione N	
Naturale Natural	Nero Black	Lunghezza Length	Larghezza Width	Max bundle Dia. mm	Min. tensile strength N	Conf. pezzi Packing pcs.
BM <b>B0824</b>	BM <b>N0824</b>	80	2,4	15	78	100/8000
BM <b>B1025</b>	BM <b>N1025</b>	100	2,5	22	80	100/5000
BM <b>B1225</b>	BM <b>N1225</b>	120	2,5	30	80	100/5000
BM <b>B1625</b>	BM <b>N1625</b>	160	2,5	40	80	100/4000
BM <b>B2025</b>	BM <b>N2025</b>	200	2,5	53	80	100/3000
BM <b>B1436</b>	BM <b>N1436</b>	140	3,6	33	180	100/2500
BM <b>B2036</b>	BM <b>N2036</b>	200	3,6	53	180	100/2000
BM <b>B2936</b>	BM <b>N2936</b>	300	3,6	76	180	100/1500
BM <b>B3736</b>	BM <b>N3736</b>	370	3,6	102	180	100
BM <b>B1248</b>	BM <b>N1248</b>	120	4,8	24	220	100/2000
BM <b>B1648</b>	BM <b>N1648</b>	160	4,8	38	220	100/1500
BM <b>B1948</b>	BM <b>N1948</b>	188	4,8	43	220	100/1500
BM <b>B2048</b>	BM <b>N2048</b>	200	4,8	50	220	100/1500
BM <b>B2548</b>	BM <b>N2548</b>	250	4,8	60	220	100/1300
BM <b>B3048</b>	BM <b>N3048</b>	300	4,8	76	220	100/1000
BM <b>B3748</b>	BM <b>N3748</b>	370	4,8	102	220	100
BM <b>B3948</b>	BM <b>N3948</b>	390	4,8	105	220	100
BM <b>B4348</b>	BM <b>N4348</b>	430	4,8	110	220	100
BM <b>B5348</b>	BM <b>N5348</b>	530	4,8	140	220	100
BM <b>B1576</b>	BM <b>N1576</b>	150	7,6	33	540	100/1000
BM <b>B2076</b>	BM <b>N2076</b>	200	7,6	50	540	100/800
BM <b>B2976</b>	BM <b>N2976</b>	300	7,6	76	540	100/600
BM <b>B3776</b>	BM <b>N3776</b>	368	7,6	102	540	100
BM <b>B4576</b>	BM <b>N4576</b>	450	7,6	132	540	100
BM <b>B5476</b>	BM <b>N5476</b>	533	7,6	140	540	100
BM <b>B7576</b>	BM <b>N7576</b>	750	7,6	218	540	100
BM <b>B4390</b>	BM <b>N4390</b>	430	9	110	790	100
BM <b>B5390</b>	BM <b>N5390</b>	526	9	140	790	100
BM <b>B7190</b>	BM <b>N7190</b>	710	9	190	790	100
BM <b>B7890</b>	BM <b>N7890</b>	776	9	228	790	100
BM <b>B8190</b>	BM <b>N8190</b>	815	9	239	790	100
BM <b>B1090</b>	BM <b>N1090</b>	1020	9	295	790	100
BM <b>B1290</b>	BM <b>N1290</b>	1220	9	365	790	100
BM <b>B1590</b>	BM <b>N1590</b>	1530	9	460	790	100

**Materiale:** Nylon 6.6 MIL-M-20693

Classe di autoestinguenza: UL 94 - V 2  
 Temperatura d'esercizio: -40°C +85°C  
 Ottima resistenza agli olii, solventi, grassi e prodotti petroliferi in genere

\* Le fascette possono essere fornite anche in buste da 1000 pezzi.  
 Per questa configurazione aggiungere la lettera M al codice prodotto.  
 Es. B0824 100 pz - B0824M 1000 pz.



Questo logo indica che i prodotti sono realizzati con materie plastiche esenti da alogeni, evitando, in caso di combustione, la formazione di gas tossici, in accordo con la norma internazionale EN 14582.

This logo indicates that the products are made with halogens free plastics, avoiding, in case of combustion, the formation of toxic gases, according to the International Standard EN 14582.

**Material:** Nylon 6.6 according to MIL-M-20693

Self extinguish UL 94 - V 2  
 Operating Temperature: -40° to +85°C  
 Resistance to the oils, greasy, solvent and petroliferous products

\* On request cable-ties are available with 1000 pcs bags.  
 Please add the letter M to article number.  
 Ex. B0824 100 pcs - B0824M 1000 pcs.